



WARNING

USE INDOORS ONLY • USE ONLY IN DRY LOCATIONS

Do not allow moisture, cleaning or other liquids to enter any of the AC or USB ports. Use this product for its intended purposes only. Dispose of packaging materials properly. Do not use plastic covering as a head cover. It may cause suffocation.

WARRANTY

The PAS311-36 is warranted from the date of purchase against failure due to materials and workmanship as follows:

- 3 years
- Indoor use only
- Dry locations only

To make a warranty claim, contact Parts Department. Provide model number, proof of purchase, description of the problem and obtain return authorization. At its option Office Star® Products will: **(a)** Supply compatible components of current manufacture **(b)** Repair the customer's component. The customer must prepay freight on any components returned to the factory. Return freight on components still in warranty will be paid by Office Star® Products.

**All warranties are limited to the original purchaser for normal commercial usage defined as a standard forty hour work week. This warranty will not cover labor, freight or damage from misuse, abuse, negligence, alteration, accident, vandalism, rusting, acts of nature or any other event beyond the control of Office Star® Products. The warranty does not cover cosmetic damage that may result from normal use. Liability for incidental or consequential damages is excluded. The user assumes all risk of injury resulting from use of this product. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.*

Our quality standards are among the highest in the industry. Sometimes, no matter how hard we try, there are times when parts are damaged or missing. Our Parts Department will do everything possible to promptly remedy the problem. Contact us via e-mail parts.department@officestar.net, by Fax 1-909-930-5629, or toll free parts number 1-800-950-7262, Monday through Friday 8:00 a.m. - 3:30 p.m. Pacific Time.

PORTS

A/C Outlets (3) NEMA 5-15R
USB Ports (1) USB Type-C, (1) USB Type-A

CORD

Usable Length 7.5 feet

ELECTRICAL RATING

Input Voltage 120V A/C, 60Hz, (12A max)

USB Ports – connected to one of two ports:

USB-C: 5V 3A, 9V 2A, 12V 1.5A, (18W max), PD 3.0

USB-A: 5V 3A, (15W max), QC 2.0/3.0

USB Ports – both ports connected:

USB-C & USB-A: 5V 3A, (15W max)

ENVIRONMENTAL

Operating 0° C to 30° C
Temperature 32° F to 86° F

Storage -10° C to 50° C
Temperature 14° F to 122° F

SAFETY STANDARDS COMPLIANCE

ETL Listed

UL962A, CUL962AL (USB ports)

UL STD1363 *Relocatable Power Taps*

CSA STDC22.2#308 *Cord Reels and Multi-Outlet Assemblies*